

Product Mark


Model: modledip24 4000k
Temperature: 20□
Tester: admin

Manufacture: LedStore.fi
Humidity: 65%
Test Date: 2018-01-02


Parameter

Name	Value	Name	Value	Name	Value
E(lx)	4574.56	Ra	96.3	Bink Freq(Hz)	-
CCT(K)	4098	S/P	1.8	Fluctuate Depth	-
Duv	0.0025	X	6651.0	Bink Percent	-
CIE(x,y)	0.3778, 0.3805	Y	6697.7	Bink Exponent	-
CIE(u,v)	0.2219, 0.3352	Z	4254.3	PAR(W/m2)	-
Dominant Wave(nm)	577.3	Rf	-	PPFD(umol/m2/s)	-
Purity	27.6%	Rg	-	YFPD(umol/m2/s)	-
Color Ratio(RGB)	19.8% 77.7% 2.6%	Ebh(mW/m2)	-	Ep(W/m2)	-
Peak Wave(nm)	451.7			Eb(W/m2)	-
Half Width(nm)	21.0			Ey(W/m2)	-
Candle E(fc)	425.15			Er(W/m2)	-
Ee(W/m2)	16.693			Erb Ratio	-



Spectrogram



CIE1931



CRI



Instrument Status

Type: LMS-6000
VDark: 2112

Integral Time: 33.000ms
Scan Range: 380-780nm

VPeak: 47120
SN: 201710272

Remark: