

Product Mark


Model: Strip 17W 4000K IP21 LedStore.fi
Temperature: 20□
Tester: LedStore.fi

Manufacture: LedStore.fi
Humidity: 65%
Test Date: 2018-08-02


Parameter

Name	Value	Name	Value	Name	Value
E(lx)	11548.19	Ra	94.8	Bink Freq(Hz)	-
CCT(K)	4198	S/P	1.9	Fluctuate Depth	-
Duv	-0.0007	X	17003.6	Bink Percent	-
CIE(x,y)	0.3717, 0.3696	Y	16908.0	Bink Exponent	-
CIE(u,v)	0.2222, 0.3314	Z	11837.9	PAR(W/m2)	-
Dominant Wave(nm)	578.7	Rf	-	PPFD(umol/m2/s)	-
Purity	22.5%	Rg	-	YFPD(umol/m2/s)	-
Color Ratio(RGB)	20.1% 77.0% 2.9%	Ebh(mW/m2)	-	Ep(W/m2)	-
Peak Wave(nm)	453.3			Eb(W/m2)	-
Half Width(nm)	24.3			Ey(W/m2)	-
Candle E(fc)	1073.25			Er(W/m2)	-
Ee(W/m2)	37.080			Erb Ratio	



Spectrogram



CIE1931



CRI



Instrument Status

Type: LMS-6000
VDark: 2005

Integral Time: 13.000ms
Scan Range: 380-780nm

VPeak: 55495
SN: 0

Remark: